


## Schottky Diodes

### 1KK2502C ~ 1KK2520C

#### ■ Features

- Reverse Voltage - 20 to 200 V
- Forward Current - 5.0 A
- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications



#### ■ Absolute Maximum Ratings and Electrical characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	1KK 2502C	1KK 2504C	1KK 2506C	1KK 2508C	1KK 2510C	1KK 2512C	1KK 2515C	1KK 2520C	Unit						
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	20	40	60	80	100	120	150	200	V						
Maximum RMS voltage	$V_{RMS}$	14	28	42	56	70	84	105	140							
Maximum DC Blocking Voltage	$V_{DC}$	20	40	60	80	100	120	150	200							
Maximum Instantaneous Forward Voltage at 5A	$V_F$	0.55		0.70		0.85										
Maximum Averaged Forward Rectified Current	$I_{F(AV)}$	5.0								A						
Peak Forward Surge Current, 8.3 ms Single Half Sine Wave Superimposed on Rated Load	$I_{FSM}$	150														
Maximum DC Reverse Current $T_a=25^\circ\text{C}$ at rated DC blocking voltage $T_a=100^\circ\text{C}$	$I_R$	1.0 50								mA						
Typical Junction Capacitance *1	$C_J$	600		400						pF						
Typical Thermal Resistance *2	$R_{\theta JA}$	35								°C/W						
Operating Junction Temperature Range	$T_J$	-55 ~ +150								°C						
Storage Temperature Range	$T_{stg}$	-55 ~ +150														

\* 1 Measured at 1MHz and applied reverse voltage of 4V D.C.

\* 2 P.C.B. mounted with 2.0" x2.0" (5x5 cm) copper pad areas.

#### ■ Marking

NO.	1KK 2502C	1KK 2504C	1KK 2506C	1KK 2508C	1KK 2510C	1KK 2512C	1KK 2515C	1KK 2520C
Marking	5C02	5C04	5C06	5C08	5C10	5C12	5C15	5C20

## Schottky Diodes

### 1KK2502C ~ 1KK2520C

#### ■ Typical Characteristics

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current




Fig.6- Typical Transient Thermal Impedance

