


## PNP Transistors

### 2SB1539

#### ■ Features

- Low collector to emitter saturation voltage
- Large collector power dissipation  $P_c$ .
- Complementary to 2SD2359



#### ■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Collector - Base Voltage	$V_{CB0}$	-20	V
Collector - Emitter Voltage	$V_{CE0}$	-20	
Emitter - Base Voltage	$V_{EB0}$	-5	
Collector Current - Continuous	$I_C$	-1	A
Collector Current - Pulse	$I_{CP}$	-1.2	
Collector Power Dissipation	$P_C$	1	W
Junction Temperature	$T_J$	150	$^\circ\text{C}$
Storage Temperature range	$T_{stg}$	-55 to 150	

#### ■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector- base breakdown voltage	$V_{CB0}$	$I_C = -100 \mu\text{A}$ , $I_E = 0$	-20			V
Collector- emitter breakdown voltage	$V_{CE0}$	$I_C = -1 \text{ mA}$ , $I_B = 0$	-20			
Emitter - base breakdown voltage	$V_{EB0}$	$I_E = -100 \mu\text{A}$ , $I_C = 0$	-5			
Collector-base cut-off current	$I_{CBO}$	$V_{CB} = -14\text{V}$ , $I_E = 0$			-1	$\mu\text{A}$
Emitter cut-off current	$I_{EBO}$	$V_{EB} = -5\text{V}$ , $I_C = 0$			-0.1	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -500 \text{ mA}$ , $I_B = -10 \text{ mA}$			-0.2	V
Base - emitter saturation voltage	$V_{BE(sat)}$	$I_C = -500 \text{ mA}$ , $I_B = -10 \text{ mA}$			-1.2	
DC current gain	$h_{FE}$	$V_{CE} = -2\text{V}$ , $I_C = -100 \text{ mA}$	200		800	
Collector output capacitance	$C_{ob}$	$V_{CB} = -10\text{V}$ , $I_E = 0$ , $f = 1\text{MHz}$		30		$\mu\text{F}$
Transition frequency	$f_T$	$V_{CE} = -10\text{V}$ , $I_E = 50 \text{ mA}$ , $f = 200\text{MHz}$		120		MHz

#### ■ Marking

Marking	1N
---------	----

# PNP Transistors

## 2SB1539

### Typical Characteristics

