



N-Channel Enhancement MOSFET

AO4886 (KO4886)

■ Features

- $V_{DS} (V) = 100V$
- $I_D = 3.3A (V_{GS} = 10V)$
- $R_{DS(ON)} < 80m\Omega (V_{GS} = 10V)$
- $R_{DS(ON)} < 91m\Omega (V_{GS} = 4.5V)$



■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current	I_D	$T_A=25^\circ C$	3.3
		$T_A=70^\circ C$	2.7
Pulsed Drain Current *1	I_{DM}	17	A
Avalanche Current *1	I_{AS}, I_{AR}	14	A
Avalanche Energy $L=0.1mH$ *1	E_{AS}, E_{AR}	10	mJ
Power Dissipation *2	P_D	$T_A=25^\circ C$	2
		$T_A=70^\circ C$	1.28
Thermal Resistance.Junction- to-Ambient *3	R_{thJA}	$t \leq 10S$	62.5
		Steady-State *4	90
Thermal Resistance.Junction- to-Case	R_{thJC}	40	$^\circ C/W$
Junction Temperature	T_J	150	
Storage Temperature Range	T_{stg}	-55 to 150	$^\circ C$

*1 Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}=150^\circ C$.

Ratings are based on low frequency and duty cycles to keep initial $T_J=25^\circ C$.

*2 The power dissipation P_D is based on $T_J(MAX)=150^\circ C$, using $\leq 10s$ junction-to-ambient thermal resistance.

*3 The value of R_{qJA} is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^\circ C$.

*4 The R_{qJA} is the sum of the thermal impedance from junction to lead R_{qJL} and lead to ambient.

N-Channel Enhancement MOSFET

AO4886 (KO4886)

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Drain-Source Breakdown Voltage	V _{DSS}	I _D =250 μA, V _{GS} =0V	100			V	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =100V, V _{GS} =0V			1	μA	
		V _{DS} =100V, V _{GS} =0V, T _J =55°C			5		
Gate-Body Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±100	nA	
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250 μA	1.6	2.2	2.7	V	
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =10V, I _D =3A		63.5	80	mΩ	
		V _{GS} =10V, I _D =3A, T _J =125°C		122	152		
		V _{GS} =4.5V, I _D =3A		70	91		
On State Drain Current	I _{D(ON)}	V _{GS} =10V, V _{DS} =5V	17			A	
Forward Transconductance	g _{FS}	V _{DS} =5V, I _D =3A		20		S	
Input Capacitance	C _{iss}	V _{GS} =0V, V _{DS} =50V, f=1MHz	620	778	942	pF	
Output Capacitance	C _{oss}		38	55	81		
Reverse Transfer Capacitance	C _{rss}		13	24	35		
Gate Resistance	R _g	V _{GS} =0V, V _{DS} =0V, f=1MHz	0.7	1.45	2.2	Ω	
Total Gate Charge (10V)	Q _g	V _{GS} =10V, V _{DS} =50V, I _D =3A	13	16.3	20	nC	
Total Gate Charge (4.5V)			6.4	8.1	10		
Gate Source Charge			Q _{gs}	2.2	2.8		3.4
Gate Drain Charge			Q _{gd}	2.4	4.1		5.8
Turn-On DelayTime	t _{d(on)}	V _{GS} =10V, V _{DS} =50V, R _L =16.7 Ω, R _{GEN} =3 Ω		6		ns	
Turn-On Rise Time	t _r			2.5			
Turn-Off DelayTime	t _{d(off)}			21			
Turn-Off Fall Time	t _f			2.4			
Body Diode Reverse Recovery Time	t _{rr}		I _F = 3A, di/dt= 500A/μs	14	21		28
Body Diode Reverse Recovery Charge	Q _{rr}	I _F = 3A, di/dt= 500A/μs	65	94	123	nC	
Maximum Body-Diode Continuous Current	I _S				2.5	A	
Diode Forward Voltage	V _{SD}	I _S =1A, V _{GS} =0V		0.74	1	V	

■ Marking

Marking	4886 KA****
---------	----------------

N-Channel Enhancement MOSFET

AO4886 (KO4886)

■ Typical Characteristics




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

N-Channel Enhancement MOSFET

AO4886 (KO4886)

■ Typical Characteristics




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Single Pulse Avalanche capability (Note C)




Figure 10: Maximum Forward Biased Safe Operating Area (Note F)




Figure 11: Single Pulse Power Rating Junction-to-Ambient (Note F)

N-Channel Enhancement MOSFET AO4886 (KO4886)

■ Typical Characteristics




Figure 12: Normalized Maximum Transient Thermal Impedance (Note F)