


Silicon Schottky Barrier Diode**HSB88WA****■ Features**

- Low reverse current, Low capacitance.
- CMPAK package is suitable for high density surface mounting and high speed assembly.

**■ Absolute Maximum Ratings Ta = 25°C**

Parameter	Symbol	Value	Unit
Reverse voltage	V _R	10	V
Average rectified current	I _o	15	mA
Junction temperature	T _j	125	°C
Storage temperature	T _{stg}	-55 to +125	°C

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward voltage	V _F	I _F = 1 mA	0.35		0.42	V
		I _F = 10 mA	0.50		0.58	
Reverse current	I _R	V _R = 2 V			0.2	μA
		V _R = 10 V			10	
Capacitance	C	V _R = 0 V, f = 1 MHz			0.80	pF
Capacitance deviation	ΔC	V _R = 0 V, f = 1 MHz			0.10	pF
Forward voltage deviation	ΔV _F	I _F = 10 mA			10	mV
ESD-Capability (Note 1)		C=200 pF, R=0 Ω Both forward and reverse direction 1 pulse.	30			V

Note

1. Failure criterion ; I_R ≥ 0.4 μA at V_R = 2 V

■ Marking

Marking	C7
---------	----